



# PHOSPAT<sup>®</sup>

## TECHNICAL DATA SHEET

### PHOSPAT<sup>®</sup> Secure 1 | 2.0

Pre-filter designed for PHOSPAT<sup>®</sup> 1 | 2.0



PHOSPAT<sup>®</sup> Secure 1 has been developed to protect PHOSPAT<sup>®</sup> 1.

Filled with VitroSphere<sup>®</sup> glass beads, it operates as pre-filter. Thus, one can protect the PHOSPAT<sup>®</sup> 1 from contamination and prevent clogging. PHOSPAT<sup>®</sup> Secure 1 may be incorporated into the existing system simply and quickly being equipped with the identical connections of the PHOSPAT<sup>®</sup> filter cartridges.

- Pre-filter for PHOSPAT<sup>®</sup> 1
- Protects PHOSPAT<sup>®</sup> 1 from contamination and clogging
- Recommended flow rate of approx. 835 l/h, backwashable
- Pressure resistance up to max. 4 bar, pressure drop about 0.1 bar
- Two 1-inch-connections / PVC-connections
- Easy plug-in with the existing system
- Protect the PHOSPAT<sup>®</sup> Secure 1 against frost.

#### Dimension & weight

Dimension (Ø x l)	80 x 470 mm
Weight	3 kg
Packaging size	530 x 90 x 90 mm

Designed and produced by:



**hydrotec**  
handels gmbh